

Electronic lift

Remote control panel

technical features

- Own-battery electric operation.
- A fully-charged battery may do up 40 to 50 journeys.
- Central control unit with battery charge level digital indicator and emergency stop button.
- Battery recharge sound indicator.
- Remote control with cable.
- Mains connection for recharge and use.
- Maximum load: 140 Kg.
- 100-mm turning wheels; the two back wheels are equipped with self-blocking brake for fixing the lift in position.
- Width-adjustable carrying base for easy access to its interior in wheelchairs or similar vehicles.
- Easily-cleaned and impermeable harnesses, made in special anti-allergy materials.
- Structure manufactured in steel tube and oven-painted with two-coats of high scratch-resistance metallic paint.
- Partially-foldable for daily storage.
- Sizes adapted for use in limited spaces.
- Total fold-up space for transport or storage (up to 155x55x35 cm).

sumax

LIFTS

This is ideal for transporting people from bed, the wheelchair, bath or car, etc. to any place that may be required.



electric system with remote control with cable.

central control unit with digital battery level viewer and recharge control.



SUMAX MODEL

operation with rechargeable batteries giving autonomy of 40-50 journeys.



mains connection which automatically recharges the battery and enables continued use of the lift.



3-position opening and closing of the carrying base.

position 1



positions 2 and 3



SUMAX / TEMPO MODEL

basic nappy-type harness allowing for two support types according to user need.



happy-type harness with head designed for those people who need comfortable head support. It allows for two support types according to user need.



very free seat and back double-support harness. The chain system allows for several support level heights.



Total lift folding

